

CISA P-KF155

Large washer-disinfector systems



High-performance bestseller

High daily productivity, optimum washing and drying, with significant savings in consumption.

The P-KF155 is the ideal choice for combining sustainability and productivity in large hospital CSSDs. Available in single door or double door system versions, it can handle loads in trays, baskets and multi-purpose and modular trolleys up to 18 DIN. The double chamber version can wash up to 36 DIN in less than an hour.



CISA P-KF155

**FAST AND SUSTAINABLE
THANKS TO FAST SYSTEM AND ECO SYSTEM**

Maximum efficiency

Ideal load capacity and washing performance for the productivity of large hospital CSSDs. Efficient, high-performance drying system in all versions without increasing space requirements.


Time saving

Washing cycle of less than 30 minutes including drying, available starting from the FAST System 2F version.




HIGH PRODUCTION CAPACITY

up to 342 DIN/trays 8h/day* with FAST and ECO System




LESS WATER CONSUMPTION

recovery of part of the water for subsequent washings with a considerable consumption saving on each cycle



LESS ENERGY CONSUMPTION

lower thermal and electrical power for water heating, and heat recovery and containment systems



LESS TIME

for water heating, up to - 20 minutes per cycle



Healthcare

Reduced consumption

The FAST System (2F) guarantees one of the lowest water consumption rates on the market: only 6 litres for thermal-disinfection of each DIN. The ECO System (3F) configuration reduces water consumption by a further 25% (up to 4.5 litres/DIN), thus reducing energy consumption and optimising the complete reprocessing process.



FAST SYSTEM 1F
Up to
-10 minutes per cycle



FAST SYSTEM 2F
Up to
-20 minutes per cycle



ECO SYSTEM 3F
Up to
-20 minutes per cycle
and up to
- 27 litres of demineralised water per cycle

**FOR AN EVEN
MORE SUSTAINABLE
RECONDITIONING PROCESS**



Fast System and Eco System

Three different configurations to implement the FAST System (1F and 2F) and the ECO System (3F), ideal for reducing loading and water heating downtime.

The FAST System and the ECO System result in a consistent reduction in total cycle time and an increase in overall productivity of up to 13%*. The ECO System option can guarantee an effective reduction of up to 27 litres of demineralised water per cycle.

SERIE CISA P-KF LARGE DIMENSIONS

18 DIN e 36 DIN****

400 and 800 liters

ALSO
DOUBLE
CAPACITY

SLIM
VERSION



Serie P-KF Models	Chamber dimensions		Overall dimensions				Chamber volume Litres	Capacity DIN trays
	LxH	P	L	H	P			
					1P	2P		
155	680	840	1200	2000	1036	1066	400	Max 18 DIN
155 Slim	x	840	883	2450	1036	1066	400	Max 18 DIN
305	630	1680	1200	2000		1910	800	Max 36 DIN

P-KF305

**DOUBLE CAPACITY: 36 DIN
IN LESS THAN AN HOUR**

P-KF155 SLIM

**AMONG THE NARROWEST
ON THE MARKET**

**DIN TRAY = 480x250x50H mm